


### Features

- Load Life : 105°C 1000hours.
- For high density mounting.
- Low impedance at 100kHz.
- Corresponding product to RoHS




### SPECIFICATION

Item	Characteristic							
Operation Temperature Range	-55 ~ +105°C							
Rated Working Voltage	6.3 ~ 50VDC							
Capacitance Tolerance (120Hz 20°C)	±20%(M)							
Leakage Current (20°C)	I ≤ 0.01CV or 3 (μA) *Whichever is greater after 2 minutes				I : Leakage Current (μA) C : Rated Capacitance (μF) V : Working Voltage (V)			
Surge Voltage (20°C)	W.V.	6.3	10	16	25	35	50	
	S.V.	8	13	20	32	44	63	
Dissipation Factor (tan δ) (120Hz 20°C)	W.V.	6.3	10	16	25	35	50	
	tan δ	0.22	0.19	0.16	0.14	0.12	0.12	
Low Temperature Stability	Impedance ratio at 120Hz							
	Rated Voltage (V)	6.3	10	16	25	35	50	
	-25°C / +20°C	2	2	2	2	2	2	
	-55°C / +20°C	5	4	4	3	3	3	
Load Life	After 1000 hours application of W.V. and +105°C ripple current value, the capacitor shall meet the following limits. (DC + ripple peak voltage ≤ rate working voltage)							
	Capacitance Change	≤ ±30% of initial value for 6.3 W.V., ≤ ±20% of initial value for 10~50 W.V.						
	Dissipation Factor	≤ 200% of initial specified value						
	Leakage current	≤ initial specified value						
Shelf Life	At +105°C, no voltage application after 1000 hours, the capacitor shall meet the limits for load life characteristics. (With voltage treatment)							
Resistance to Soldering Heat	Capacitor placed on a 250°C hot plate for 30 seconds with their electrode terminals facing downward will fulfill the following conditions after being cooled to room temperature.							
	Capacitance Change	≤ ±10% of initial value						
	Dissipation Factor	≤ initial specified value						
	Leakage current	≤ initial specified value						

### DIMENSIONS (mm)

D	L	A	H	I	W	P	K
4.0	5.4	4.3	5.5MAX	1.8	0.65±0.1	1.0	0.35 <sup>+0.15</sup> <sub>-0.20</sub>
5.0	5.4	5.3	6.5MAX	2.2	0.65±0.1	1.5	0.35 <sup>+0.15</sup> <sub>-0.20</sub>
6.3	5.4	6.6	7.8MAX	2.6	0.65±0.1	2.1	0.35 <sup>+0.15</sup> <sub>-0.20</sub>



● CASE SIZE & MAX RIPPLE CURRENT

Case size : D x L (mm)  
 Max impedance : Ω 20°C 100kHz  
 Max ripple current : mA(rms) 105°C 100kHz

μF	V(DC) Item	6.3			10			16			25			35			50		
		DxL	IMP.	R.C.															
1.0														4x5.4	3.9	60	4x5.4	4.9	30
2.2														4x5.4	3.6	60	4x5.4	4.5	30
3.3														4x5.4	3.0	60	4x5.4	3.7	30
4.7											4x5.4	3.1	60	4x5.4	2.5	60	5x5.4	3.1	41
6.8											4x5.4	2.7	60	5x5.4	2.2	60	6.3x5.4	2.7	55
10								4x5.4	3.3	60	5x5.4	2.4	65	5x5.4	1.9	70	6.3x5.4	2.4	70
22		4x5.4	3.2	60	5x5.4	2.2	65	5x5.4	1.8	85	6.3x5.4	1.3	110	6.3x5.4	1.0	120			
33		5x5.4	2.4	65	5x5.4	1.7	75	6.3x5.4	1.4	120	6.3x5.4	1.0	140						
47		5x5.4	2.0	80	6.3x5.4	1.4	110	6.3x5.4	1.1	140									
68		6.3x5.4	1.5	110	6.3x5.4	1.1	130												
100		6.3x5.4	1.2	130	6.3x5.4	0.9	150												